

Jetta Hybrid		110 kW (150 PS)
Engine, electrics		
Type of engine		4-cyl. petrol engine TSI Hybrid
Engine position		Front transverse installation
Material of cylinder head and engine block		Aluminium alloy/grey cast iron casting
Bore/stroke	mm	74.5/80
Effective displacement	cm ³	1,395
Valves per cylinder, drive		4 at an angle/indirect, roller rocker finger
Number of camshafts, position, drive		2/in cylinder head/toothed belt driven
Compression ratio	:1	10
Mixture formation		Direct petrol injection
Type of charging and pressure		Turbocharger/charge pressure
Emissions control system		3-way catalytic converter with Lambda probe
Power output	kW (PS) at rpm	110 (150) 5,000 1)
Max. torque	Nm at rpm	250/1,600-3,500 2)
Alternator	A	-
Battery, capacity	A(Ah)	280 (60)
Performance (at curb weight + 200 kg)		
Acceleration 0 - 80/100 km/h	s	6.2/8.6
Acceleration 0 - 400/1000 m/s	s	/
Top speed	km/h	210
Stationary noise/driving noise	dB(A)	74/69
Fuel consumption (99/100/EC)		
Fuel type		Premium 95 RON
Urban	l/100km	4.4
Extra-urban	l/100km	3.9
Combined cycle	l/100km	4.1
Emissions (CO ₂ /HC/NO _x /HC+NO _x /particulates)	g/km	95/0.05/0.01/ /0
Efficiency label		A+
Exhaust emissions classification		Euro 6
Power transmission		
Type of clutch		Two electrohydraulically operated dry clutches
Gearbox		Seven-speed direct shift gearbox (DSG)
Individual/overall ratio, 1st gear	:1	3.5/15.533
Individual/overall ratio, 2nd gear	:1	2.087/9.262
Individual/overall ratio, 3rd gear	:1	1.343/5.96
Individual/overall ratio, 4th gear	:1	0.933/4.141
Individual/overall ratio, 5th gear	:1	0.974/3.143
Individual/overall ratio, 6th gear	:1	0.778/2.511
Individual/overall ratio, 7th gear	:1	0.653/2.107
Individual/overall ratio, reverse gear	:1	3.722/15.543
Front final drive ratio, output shafts 1/2/3		4.438/3.227/4.176
Gears on output shafts 1/2/3		1st-4th gears/5th-7th gears/rev. gear
Running gear		Front: McPherson struts with lower wishbones. Rear: four-link suspension with separate spring/shock absorber arrangement, anti-roll bars front and rear. ESP, TSC electromechanical servotronic steering with speed-dependent power assistance.
Wheels		6 J x 15
Tyres		195/65 R 15 H
Brakes		
Brakes		Disc brakes front and rear, front discs ventilated, ABS, EBPD, dual brake assist.
Type of ABS		Hydraulic ABS system
Ø Discs/drums front/rear	mm	288/253
Wheels to which parking brake is applied		Rear wheels
Exterior dimensions		
Number of doors		4
Length/width/height	mm	4,644/1,778/1,482
Wheelbase	mm	2,651
Track, front/rear	mm	1,535/1,538
Turning circle	m	11.1
Steering ratio		14.96
Interior dimensions		
Number of seats		5
Front entry, width/height	mm	-/-
Rear entry, width/height	mm	-/-
Elbow width at front/rear	mm	1,447/1,434
Luggage compartment		
Length, rear seat raised/folded down	mm	1,058/1,884
Smallest luggage compartment width	mm	1,008
Height	mm	347
Volume by VDA measurement: rear seat raised/folded down	l	374
Width of tailgate	mm	/992
Weights		
Unladen weight	kg	1,505
Permitted gross weight	kg	2,020
Payload	kg	590
Perm. axle load, front/rear	kg	990/1,080
Perm. trailer load up to 12%, braked/unbraked	kg	-/-
Perm. drawbar weight/roof load	kg	-/75
Capacities		
Fuel tank	l	45
Service		
Oil change interval	km	Depending up on service indicator
Inspection interval		Depending up on service indicator
Warranty		2 years unlimited mileage, 3 years paintwork, 12 years
Insurance classification		body perforation, mobility guarantee 23/19/18

1) E-engine power output kW (PS): 20 (27), power output (Boosten) kW (PS): 125 (170)

2) Max. torque (Boosten): Nm at rpm 250/2.500